

► HF429

# PP

#### Homo PP for Casting Film

#### Description

**HF429** is a high isotactic polypropylene, homopolymer having excellent heat resistance as well as superior flexural modulus.

# Characteristics

- ► High stiffness
- Excellent heat resistance

# Physical Properties

| <b>Typical Properties</b>  | Method<br>(ASTM) | Unit               | HF429  |
|----------------------------|------------------|--------------------|--------|
| Melt flow index            | D1238            | g/10min            | 8.0    |
| Density                    | D1505            | g/cm <sup>3</sup>  | 0.91   |
| Tensile strength at yield  | D638             | kg/cm <sup>2</sup> | 410    |
| Elongation at break        | D638             | %                  | 500    |
| Flexural modulus           | D790             | kg/cm <sup>2</sup> | 18,000 |
| Izod impact strength 23 °C | D256             | kgcm/cm            | 3.0    |
| Rockwell hardness          | D785             | R-scale            | 107    |
| Heat distortion temp.      | D648             | C                  | 125    |

\* Data shown above are representative values for reference purposes only, and not to be construed as specifications.

\* Data performed by or on behalf of Hanwha Total



# Food Contact Application

- Hanwha Total HF429 meets the FDA requirements in the Code of Federal Regulations in 21 CFR 177.1520 for food contact.
- In case you might need additional technical or regulatory information, please contact Hanwha Total Polymer Technical Service Team.

# Contacts

#### Product Information & Technical Services

103, Dokgot 2-ro, Daesan-eup, Seosan-si, Chungcheongnam-do, Korea, 31900 TEL : 82-41-660-6190 FAX : 82-41-660-6189

#### Disclaimer

This document is copyright of Hanwha Total petrochemicals Co., Ltd. Any and all information and the values in this document are typical properties for reference, not to be confused with, or regarded as specification. Customers are responsible for determining whether our products and information are suitable for their particular purpose and for ensuring that Customer's location and handling practices are in compliance with laws and regulations. HANWHA TOTAL assumes no obligation or liability for the information in this document. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY HANWHA TOTAL. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. HANWHA TOTAL is entitled to alter, change or modify any of the content herein at any time without prior notice, but not under any duty to do so.